

PRODUCT-DETAILS

SPL20/3M

SPL20 3M CUT LENGTH



General Information

Extended Product Type	SPL20/3M
Product ID	7TCA296030R0142
EAN	5020963019937
Catalog Description	SPL20 3M CUT LENGTH
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 3 Meters, PVC Covering with Galvanised Steel Core, Black

Ordering

EAN	5020963019937
-----	---------------

Dimensions

Product Net Depth / Length	3 m
Product Net Weight	2.63 lb 1.193 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	15.9 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.1 mm
Product Name	ADAPTAFLEX
Product Type	Oil Resistant Conduit
Radius	80 mm
UPC	786210275079

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL20/3M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL20/3M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

