

PRODUCT-DETAILS

# SPL20/4M

## SPL20 4 CUT LENGTH



### General Information

Extended Product Type	SPL20/4M
Product ID	7TCA296030R0143
EAN	5020963021084
Catalog Description	SPL20 4 CUT LENGTH
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 4 Meters, PVC Covering with Galvanised Steel Core, Black

### Ordering

EAN	5020963021084
-----	---------------

### Dimensions

Product Net Depth / Length	4 m
Product Net Weight	3.51 lb 1.592 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	15.9 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.1 mm
Product Name	ADAPTAFLEX
Product Type	Oil Resistant Conduit
Radius	80 mm
UPC	786210275086

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL20/4M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL20/4M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

