

PRODUCT-DETAILS

# SPL20/E

## SPL20 ENTRY GLAND



### General Information

Extended Product Type	SPL20/E
Product ID	7TCA296030R0147
EAN	5020963011610
Catalog Description	SPL20 ENTRY GLAND
Long Description	Nickel Plated Brass Conduit Entry Gland, Nominal Conduit Size 20 Millimeters

### Ordering

EAN	5020963011610
-----	---------------

### Dimensions

Product Net Weight	.017 lb 7.71 g
--------------------	-------------------

### Container Information

Package Level 1 Units	10 piece
Package Level 2 Units	1000 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm

Package Level 2 Depth /  
Length

1 in  
25 mm

---

## Additional Information

Application	Cable Protection at Conduit Entry / Exit Point
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP54
Material	Brass
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Conduit Terminator
Size	1/2 Inch
Special Functions	Very High UV Protection and High Degree of Mechanical Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -65 to +300 °C
UPC	786210246772

---

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL20/E
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL20/E

---

## Classifications

ETIM 6	EC000814 - Threaded bush
ETIM 7	EC000814 - Threaded bush
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

---

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

