

PRODUCT-DETAILS

SPL25/50M

50M X SPL25/BLACK CONDUIT



General Information

Extended Product Type	SPL25/50M
Product ID	7TCA296030R0195
EAN	5020963000324
Catalog Description	50M X SPL25/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 50 Meters, PVC Covering with Galvanised Steel Core, Black

Ordering

EAN	5020963000324
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	56.99 lb 25.846 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	37 in 940 mm

Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	7 in 178 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	21.0 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	3/4 in NC25
Number of Batteries	0
Outside Diameter	26.4 mm
Product Name	flexible metal conduit
Product Type	Oil Resistant Conduit
Radius	110 mm
UPC	786210247069

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL25/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL25/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

