

PRODUCT-DETAILS

SPL25/8M

SPL25 8M CUT LENGTH



General Information

Extended Product Type	SPL25/8M
Product ID	7TCA296030R0197
EAN	5020963031595
Catalog Description	SPL25 8M CUT LENGTH
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 8 Meters, PVC Covering with Galvanised Steel Core, Black

Ordering

EAN	5020963031595
-----	---------------

Dimensions

Product Net Depth / Length	8 m
Product Net Weight	9.12 lb 4.136 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	21.0 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	3/4 in NC25
Number of Batteries	0
Outside Diameter	26.4 mm
Product Name	ADAPTAFLEX
Product Type	Oil Resistant Conduit
Radius	110 mm
UPC	786210275154

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL25/8M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL25/8M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

