

PRODUCT-DETAILS

SPL25/GR/10M

SPL LQT FLEXIBLE 10M REELS



General Information

Extended Product Type	SPL25/GR/10M
Product ID	7TCA296030R0201
EAN	5020963026829
Catalog Description	SPL LQT FLEXIBLE 10M REELS
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 10 Meters, PVC Covering with Galvanised Steel Core, Grey

Ordering

EAN	5020963026829
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	11.4 lb 5.17 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Gray
Flexibility	Medium
Inside Diameter	21.0 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	3/4 in NC25
Number of Batteries	0
Outside Diameter	26.4 mm
Product Name	ADAPTAFLEX
Product Type	Oil Resistant Conduit
Radius	110 mm
UPC	786210275109

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL25/GR/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL25/GR/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

