

PRODUCT-DETAILS

# SPL25/OR/25M

## SPL25/ORANGE NC25 25M COILS



### General Information

Extended Product Type	SPL25/OR/25M
Product ID	7TCA296030R0221
EAN	5020963010774
Catalog Description	SPL25/ORANGE NC25 25M COILS
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Orange

### Ordering

EAN	5020963010774
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	27.01 lb 12.249 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Orange
Flexibility	Medium
Inside Diameter	21.0 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	3/4 in NC25
Number of Batteries	0
Outside Diameter	26.4 mm
Product Name	STEEL FLEX ELECT.CONDUIT PVC JACKET
Product Type	Oil Resistant Conduit
Radius	110 mm
UPC	786210239477

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL25/OR/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL25/OR/25M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

