

PRODUCT-DETAILS

# SPL32/10M

## 10M X SPL32/BLACK CONDUIT



### General Information

Extended Product Type	SPL32/10M
Product ID	7TCA296030R0236
EAN	5020963000997
Catalog Description	10M X SPL32/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, Nominal Conduit Size 32mm, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 10 Meters, PVC Covering with Galvanised Steel Core, Black

### Ordering

EAN	5020963000997
-----	---------------

### Dimensions

Product Net Depth / Length	10 m
Product Net Weight	19.84 lb 8.998 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	26.7 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1 in NC32
Number of Batteries	0
Outside Diameter	33.1 mm
Product Name	flexible metal conduit
Product Type	Oil Resistant Conduit
Radius	145 mm
UPC	786210247168

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL32/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL32/10M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

