

PRODUCT-DETAILS

SPL32/25M

25M X SPL32/BLACK CONDUIT



General Information

Extended Product Type	SPL32/25M
Product ID	7TCA296030R0238
EAN	5020963000577
Catalog Description	25M X SPL32/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, Nominal Conduit Size 32mm, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Black

Ordering

EAN	5020963000577
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	36.37 lb 16.494 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	18 in 457 mm

Package Level 1 Height	14 in 356 mm
Package Level 1 Depth / Length	18 in 457 mm
Package Level 2 Units	10 piece
Package Level 2 Width	40 in 1016 mm
Package Level 2 Height	50 in 1270 mm
Package Level 2 Depth / Length	48 in 1219 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	26.7 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1 in NC32
Number of Batteries	0
Outside Diameter	33.1 mm
Product Name	flexible metal conduit
Product Type	Oil Resistant Conduit
Radius	145 mm
UPC	786210247182

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL32/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL32/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

