

PRODUCT-DETAILS

SPL32/OR/25M

SPL32/ORANGE NC32 25M COILS



General Information

Extended Product Type	SPL32/OR/25M
Product ID	7TCA296030R0261
EAN	5020963008849
Catalog Description	SPL32/ORANGE NC32 25M COILS
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 32mm, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Orange

Ordering

EAN	5020963008849
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	38.14 lb 17.297 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Orange
Flexibility	Medium
Inside Diameter	26.7 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1 in NC32
Number of Batteries	0
Outside Diameter	33.1 mm
Product Name	STEEL FLEX ELECT.CONDUIT PVC JACKET
Product Type	Oil Resistant Conduit
Radius	145 mm
UPC	786210239514

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL32/OR/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL32/OR/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

