

PRODUCT-DETAILS

# SPL40/25M

## 25M X SPL40/BLACK CONDUIT



### General Information

Extended Product Type	SPL40/25M
Product ID	7TCA296030R0270
EAN	5020963000973
Catalog Description	25M X SPL40/BLACK CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 40mm, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 180mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Black

### Ordering

EAN	5020963000973
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	52.9 lb 23.991 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	35.4 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1-1/4 in NC40
Number of Batteries	0
Outside Diameter	41.8 mm
Product Name	flexible metal conduit
Product Type	Oil Resistant Conduit
Radius	180 mm
UPC	786210247243

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL40/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL40/25M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

