

PRODUCT-DETAILS

# SPL40/GR/25M

## 25M X SPL40/GREY CONDUIT



Product image  
not available

### General Information

Extended Product Type	SPL40/GR/25M
Product ID	7TCA296030R0278
EAN	5020963798924
Catalog Description	25M X SPL40/GREY CONDUIT
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 40mm, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 180mm, Reel Length 10 Meters, PVC Covering with Galvanised Steel Core, Grey

### Ordering

EAN	5020963798924
-----	---------------

### Dimensions

Product Net Depth / Length	10 m
Product Net Weight	77.53 lb 35.161 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Gray
Flexibility	Medium
Inside Diameter	35.4 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1-1/4 in NC40
Number of Batteries	0
Outside Diameter	41.8 mm
Product Name	LIQUID TIGHT CONDUIT
Product Type	Oil Resistant Conduit
Radius	180 mm
UPC	786210293646

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL40/GR/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL40/GR/25M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image  
not available