

PRODUCT-DETAILS

SPL50/150/M

BRASS LQT M TYPE FITTING 1.5



General Information

Extended Product Type	SPL50/150/M
Product ID	7TCA296030R0290
EAN	5020963789564
Catalog Description	BRASS LQT M TYPE FITTING 1.5
Long Description	Nickel Plated Brass Liquid Tight Straight Swivel Fitting with External Thread, Nominal Conduit Size 50 Millimeters, NPT Thread Size 1-1/2 Inch

Ordering

EAN	5020963789564
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	.74 lb 335.601 g

Container Information

Package Level 2 Units	20 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	40.4 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1-1/2 in NC50
Number of Batteries	0
Outside Diameter	47.5 mm
Product Name	ADAPTAFLEX
Product Type	Oil Resistant Conduit
Radius	240 mm
UPC	786210247274

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK107492A2426
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL50/150/M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

