

PRODUCT-DETAILS

SPL50/OR/25M

SPL50/ORNGE NC50 25M REELS



General Information

Extended Product Type	SPL50/OR/25M
Product ID	7TCA296030R0307
EAN	5020963016929
Catalog Description	SPL50/ORNGE NC50 25M REELS
Long Description	Liquid Tight, Oil Resistant, Medium Flexibility Conduit, Nominal Conduit Size 50mm, Outside Diameter 47.5mm, Inside Diameter 40.4mm, Static Bend Radius 240mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Orange

Ordering

EAN	5020963016929
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	64.19 lb 29.111 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Orange
Flexibility	Medium
Inside Diameter	40.4 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	1-1/2 in NC50
Number of Batteries	0
Outside Diameter	47.5 mm
Product Name	ADAPTAFLEX
Product Type	Oil Resistant Conduit
Radius	240 mm
UPC	786210275239

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL50/OR/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL50/OR/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

