

PRODUCT-DETAILS

SPL63/E

SPL63/M/INSERT



General Information

Extended Product Type	SPL63/E
Product ID	7TCA296030R0316
EAN	5020963033247
Catalog Description	SPL63/M/INSERT
Long Description	Nickel Plated Brass Conduit Terminator, Nominal Conduit Size 63 Millimeters

Ordering

EAN	5020963033247
-----	---------------

Dimensions

Product Net Weight	.18 lb 81.633 g
--------------------	--------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm
Package Level 2 Depth /	1 in

Length 25 mm

Additional Information

Application	Cable Protection at Conduit Entry / Exit Point
Brand / Label	Adaptaflex
Color	Metallic
Insulation Class	IP54
Material	Brass
Number of Batteries	0
Product Name	ADAPTAFLEX
Product Type	Conduit Terminator
Size	2 Inch
Special Functions	Very High UV Protection and High Degree of Mechanical Protection
Surface Finishing	Nickel Plated
Temperature Range	Static -65 to +300 °C
UPC	786210239538

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL63/E
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL63/E

Classifications

ETIM 6	EC000814 - Threaded bush
ETIM 7	EC000814 - Threaded bush
UNSPSC	39121312
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4442 >> Electrical bushing

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

