

PRODUCT-DETAILS

SPL63/OR/25M

SPL63/ORNGE IN 25M COILS



General Information

Extended Product Type	SPL63/OR/25M
Product ID	7TCA296030R0324
EAN	5020963016936
Catalog Description	SPL63/ORNGE IN 25M COILS
Long Description	Liquid Tight Oil Resistant Covered Steel Flexible Conduit, Nominal Conduit Size 63mm, Outside Diameter 59.7mm, Inside Diameter 51.6mm, Static Bend Radius 345mm, Reel Length 25 Meters, PVC Covered Galvanised Steel, Orange

Ordering

EAN	5020963016936
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	80.41 lb 36.467 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Liquid Tight - Indoors / Outdoors, Marine, Buildings
Brand / Label	Adaptaflex
Color	Orange
Flexibility	Medium
Inside Diameter	51.6 mm
Material	Galvanized Steel Core with PVC Covering
Nominal Size	2 in NC63
Number of Batteries	0
Outside Diameter	59.7 mm
Product Name	STEEL FLEX CONDUIT WITH PVC JACKET
Product Type	Oil Resistant Conduit
Radius	345 mm
UPC	786210275277

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPL63/OR/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPL63/OR/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

