

PRODUCT-DETAILS

# SPLHC10/25M

## 25M X SPLHC10 CONDUIT



### General Information

Extended Product Type	SPLHC10/25M
Product ID	7TCA296030R0330
EAN	5020963035197
Catalog Description	25M X SPLHC10 CONDUIT
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 10mm, Outside Diameter 11.8mm, Inside Diameter 7.0mm, Static Bend Radius 40mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

### Ordering

EAN	5020963035197
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	8.93 lb 4.05 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	7.0 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	1/4 in NC10
Number of Batteries	0
Outside Diameter	11.8 mm
Product Name	flexible metal conduit
Product Type	Extreme Temperature Flexible Conduit
Radius	40 mm
UPC	786210245584

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC10/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHC10/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

