

PRODUCT-DETAILS

SPLHC16/25M

25M X SPLHC16 CONDUIT



General Information

Extended Product Type	SPLHC16/25M
Product ID	7TCA296030R0335
EAN	5020963009822
Catalog Description	25M X SPLHC16 CONDUIT
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 16mm, Outside Diameter 17.8mm, Inside Diameter 12.5mm, Static Bend Radius 50mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Ordering

EAN	5020963009822
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	17.44 lb 7.909 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	12.5 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	3/8 in NC16
Number of Batteries	0
Outside Diameter	17.8 mm
Product Name	flexible metal conduit
Product Type	Extreme Temperature Flexible Conduit
Radius	50 mm
UPC	786210245614

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC16/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHC16/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

