

PRODUCT-DETAILS

# SPLHC16/50M

## HIGH TEMP LIQUIDTIGHT CONDUIT



### General Information

Extended Product Type	SPLHC16/50M
Product ID	7TCA296030R0336
EAN	5020963007019
Catalog Description	HIGH TEMP LIQUIDTIGHT CONDUIT
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 16mm, Outside Diameter 17.8mm, Inside Diameter 12.5mm, Static Bend Radius 50mm, Reel Length 50 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

### Ordering

EAN	5020963007019
-----	---------------

### Dimensions

Product Net Depth / Length	50 m
Product Net Weight	32.41 lb 14.698 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	12.5 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	3/8 in NC16
Number of Batteries	0
Outside Diameter	17.8 mm
Product Name	ADAPTAFLEX
Product Type	Extreme Temperature Flexible Conduit
Radius	50 mm
UPC	786210274799

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC16/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHC16/50M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

