

PRODUCT-DETAILS

SPLHC25/100M

LTIGHT COND HIGHTEMP 25MM BLK 100M



General Information

Extended Product Type	SPLHC25/100M
Product ID	7TCA296030R0342
EAN	5020963050381
Catalog Description	LTIGHT COND HIGHTEMP 25MM BLK 100M
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 100 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Ordering

EAN	5020963050381
-----	---------------

Dimensions

Product Net Depth / Length	100 m
Product Net Weight	107.37 lb 48.694 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	21.0 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	3/4 in NC25
Number of Batteries	0
Outside Diameter	26.4 mm
Product Name	flexible metal conduit
Product Type	Extreme Temperature Flexible Conduit
Radius	110 mm
UPC	786210245669

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC25/100M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHC25/100M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

