

PRODUCT-DETAILS

# SPLHC32/25M

## 25M X SPLHC32 CONDUIT



### General Information

Extended Product Type	SPLHC32/25M
Product ID	7TCA296030R0348
EAN	5020963008047
Catalog Description	25M X SPLHC32 CONDUIT
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 32mm, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

### Ordering

EAN	5020963008047
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	33.94 lb 15.392 kg

### Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	9 in

Package Level 1 Height	229 mm 25 in 635 mm
Package Level 1 Depth / Length	25 in 635 mm
Package Level 2 Units	10 piece
Package Level 2 Width	9.5 in 241 mm
Package Level 2 Height	25 in 635 mm
Package Level 2 Depth / Length	25 in 635 mm

## Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	26.7 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	1 in NC32
Number of Batteries	0
Outside Diameter	33.1 mm
Product Name	BRADED FLEX CONDUIT, STEEL
Product Type	Extreme Temperature Flexible Conduit
Radius	145 mm
UPC	786210258942

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC32/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHC32/25M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

