

PRODUCT-DETAILS

SPLHC32/50M

32MM LIQUID TIGHT CONDUITHIGH TEMPE



General Information

Extended Product Type	SPLHC32/50M
Product ID	7TCA296030R0350
EAN	5020963050763
Catalog Description	32MM LIQUID TIGHT CONDUITHIGH TEMPE
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 32mm, Outside Diameter 33.1mm, Inside Diameter 26.7mm, Static Bend Radius 145mm, Reel Length 50 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Ordering

EAN	5020963050763
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	74.63 lb 33.846 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	26.7 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	1 in NC32
Number of Batteries	0
Outside Diameter	33.1 mm
Product Name	flexible metal conduit
Product Type	Extreme Temperature Flexible Conduit
Radius	145 mm
UPC	786210245690

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC32/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHC32/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

