

PRODUCT-DETAILS

# SPLHC40/30M

## SPLHC40 COND 30M COIL



Product image  
not available

---

### General Information

Extended Product Type	SPLHC40/30M
Product ID	7TCA296030R0353
EAN	5020963778001
Catalog Description	SPLHC40 COND 30M COIL
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 40mm, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 180mm, Reel Length 30 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

---

### Ordering

EAN	5020963778001
-----	---------------

---

### Dimensions

Product Net Depth / Length	30 m
Product Net Weight	71.76 lb 32.544 kg

---

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	35.4 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	1-1/4 in NC40
Number of Batteries	0
Outside Diameter	41.8 mm
Product Name	metal flex conduit
Product Type	Extreme Temperature Flexible Conduit
Radius	180 mm
UPC	786210274829

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC40/30M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHC40/30M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image  
not available