

PRODUCT-DETAILS

SPLHC50/25M

25M X SPLHC50 CONDUIT



General Information

Extended Product Type	SPLHC50/25M
Product ID	7TCA296030R0357
EAN	5020963013775
Catalog Description	25M X SPLHC50 CONDUIT
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 50mm, Outside Diameter 47.9mm, Inside Diameter 40.4mm, Static Bend Radius 240mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Ordering

EAN	5020963013775
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	62 lb 28.118 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	40.4 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	1-1/2 in NC50
Number of Batteries	0
Outside Diameter	47.9 mm
Product Name	ADAPTAFLEX
Product Type	Extreme Temperature Flexible Conduit
Radius	240 mm
UPC	786210258959

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC50/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHC50/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

