

PRODUCT-DETAILS

# SPUL16/25M

## UL LISTED 16MM LIQUIDTIGHT CONDUIT



### General Information

Extended Product Type	SPUL16/25M
Product ID	7TCA296030R0365
EAN	5020963006401
Catalog Description	UL LISTED 16MM LIQUIDTIGHT CONDUIT
Long Description	Liquid Tight, Medium Flexibility, Covered Steel Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.8mm, Inside Diameter 12.8mm, Static Bend Radius 50mm, Reel Length 25 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Grey

### Ordering

EAN	5020963006401
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	19.84 lb 8.998 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

## Additional Information

Application	Flexible Protection Systems
Brand / Label	Adaptaflex
Color	Gray
Flexibility	Medium
Inside Diameter	12.8 mm
Material	Galvanized Steel Core with PVC Cover and Copper Packing
Nominal Size	3/8 in NC16
Number of Batteries	0
Outside Diameter	17.8 mm
Product Name	ADAPTAFLEX
Product Type	Liquid Tight, Medium Flexibility Conduit
Radius	50 mm
Special Functions	High UV Protection
Standards	UL Listed, CSA
UPC	786210275291

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPUL16/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPUL16/25M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

