

PRODUCT-DETAILS

# SPUL25/50M

## NC25 LQT CONDUIT 50M COIL



### General Information

Extended Product Type	SPUL25/50M
Product ID	7TCA296030R0369
EAN	5020963004520
Catalog Description	NC25 LQT CONDUIT 50M COIL
Long Description	Liquid Tight, Medium Flexibility, Covered Steel Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 105mm, Reel Length 50 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Grey

### Ordering

EAN	5020963004520
-----	---------------

### Dimensions

Product Net Depth / Length	50 m
Product Net Weight	94.03 lb 42.644 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Flexible Protection Systems
Brand / Label	Adaptaflex
Color	Gray
Flexibility	Medium
Inside Diameter	21.0 mm
Material	Galvanized Steel Core with PVC Cover and Copper Packing
Nominal Size	3/4 in NC25
Number of Batteries	0
Outside Diameter	26.4 mm
Product Name	ADAPTAFLEX
Product Type	Liquid Tight, Medium Flexibility Conduit
Radius	105 mm
Special Functions	High UV Protection
Standards	UL Listed, CSA
UPC	786210275314

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPUL25/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPUL25/50M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

