

PRODUCT-DETAILS

SPUL40/25M

FLEX COND TO UL SPEC NC40 25M



General Information

Extended Product Type	SPUL40/25M
Product ID	7TCA296030R0372
EAN	5020963008399
Catalog Description	FLEX COND TO UL SPEC NC40 25M
Long Description	Liquid Tight, Medium Flexibility, Covered Steel Conduit, Nominal Conduit Size 40mm, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 200mm, Reel Length 25 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Grey

Ordering

EAN	5020963008399
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	92.85 lb 42.109 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Flexible Protection Systems
Brand / Label	Adaptaflex
Color	Gray
Flexibility	Medium
Inside Diameter	35.4 mm
Material	Galvanized Steel Core with PVC Cover and Copper Packing
Nominal Size	1-1/4 in NC40
Number of Batteries	0
Outside Diameter	41.8 mm
Product Name	flexible metal conduit
Product Type	Liquid Tight, Medium Flexibility Conduit
Radius	200 mm
Special Functions	High UV Protection
Standards	UL Listed, CSA
UPC	786210247588

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPUL40/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPUL40/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

