

PRODUCT-DETAILS

SPUL63/10M

FLEX COND TO UL SPEC NC63 10M



General Information

Extended Product Type	SPUL63/10M
Product ID	7TCA296030R0376
EAN	5020963009082
Catalog Description	FLEX COND TO UL SPEC NC63 10M
Long Description	Liquid Tight, Medium Flexibility, Covered Steel Conduit, Nominal Conduit Size 63mm, Outside Diameter 60.0mm, Inside Diameter 51.6mm, Static Bend Radius 355mm, Reel Length 10 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Grey

Ordering

EAN	5020963009082
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	1 lb 453.515 g

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Flexible Protection Systems
Brand / Label	Adaptaflex
Color	Gray
Flexibility	Medium
Inside Diameter	51.6 mm
Material	Galvanized Steel Core with PVC Cover and Copper Packing
Nominal Size	2 in NC63
Number of Batteries	0
Outside Diameter	60.0 mm
Product Name	ADAPTAFLEX
Product Type	Liquid Tight, Medium Flexibility Conduit
Radius	355 mm
Special Functions	High UV Protection
Standards	UL Listed, CSA
UPC	786210275345

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPUL63/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPUL63/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

