

PRODUCT-DETAILS

SPLHC12/70M

THERMOPLASTIC COVERED GALV STEEL



General Information

Extended Product Type	SPLHC12/70M
Product ID	7TCA296030R0388
EAN	5020963799983
Catalog Description	THERMOPLASTIC COVERED GALV STEEL
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 12mm, Outside Diameter 14.2mm, Inside Diameter 12.0mm, Static Bend Radius 45mm, Reel Length 70 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Ordering

EAN	5020963799983
-----	---------------

Dimensions

Product Net Depth / Length	70 m
Product Net Weight	35.06 lb 15.9 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	12.0 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	5/16 in NC12
Number of Batteries	0
Outside Diameter	14.2 mm
Product Name	THERMOPLASTIC COVERED GALV STEEL
Product Type	Extreme Temperature Flexible Conduit
Radius	45 mm
UPC	786210313979

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC12/70M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHC12/70M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

