

PRODUCT-DETAILS

SPLHC16/100M

H/T LQT CONDUIT 100M REEL



General Information

Extended Product Type	SPLHC16/100M
Product ID	7TCA296030R0389
EAN	5020963800030
Catalog Description	H/T LQT CONDUIT 100M REEL
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 16mm, Outside Diameter 17.8mm, Inside Diameter 12.5mm, Static Bend Radius 50mm, Reel Length 100 Meters, Thermoplastic Rubber Cover with Galvanised Steel Core, Black

Ordering

EAN	5020963800030
-----	---------------

Dimensions

Product Net Depth / Length	100 m
Product Net Weight	64.82 lb 29.397 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	16 in

	406 mm
Package Level 2 Height	16 in
	406 mm
Package Level 2 Depth / Length	16 in
	406 mm

Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	12.5 mm
Material	Galvanized Steel Core with Thermoplastic Rubber Cover
Nominal Size	3/8 in NC16
Number of Batteries	0
Outside Diameter	17.8 mm
Product Name	FLEXIBLE METAL CONDUIT
Product Type	Extreme Temperature Flexible Conduit
Radius	50 mm
UPC	786210253855

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPLHC16/100M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPLHC16/100M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

