

PRODUCT-DETAILS

LFH-SPL16/10M

16MM LOW FIRE HAZARD LT COND 10M



Product image
not available

General Information

Extended Product Type	LFH-SPL16/10M
Product ID	7TCA296030R0401
EAN	5020963800689
Catalog Description	16MM LOW FIRE HAZARD LT COND 10M
Long Description	Liquid Tight, Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.0mm, Inside Diameter 13.0mm, Static Bend Radius 50mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 10 Meters, Black

Ordering

EAN	5020963800689
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	6.77 lb 3.07 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	6 in 152 mm

Package Level 2 Height	16 in 406 mm
Package Level 2 Depth / Length	16 in 406 mm

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	13.0 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	3/8 in NC16
Number of Batteries	0
Outside Diameter	17.0 mm
Product Name	Flexible Metal Conduit
Product Type	Low Fire Hazard Conduit
Radius	50 mm
Special Functions	High UV Protection
UPC	786210289670

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SPL16/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SPL16/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available