

PRODUCT-DETAILS

LFH-SPL20/10M

20MM LOW FIRE HAZARD LT COND 10M



Product image
not available

General Information

Extended Product Type	LFH-SPL20/10M
Product ID	7TCA296030R0403
EAN	5020963800702
Catalog Description	20MM LOW FIRE HAZARD LT COND 10M
Long Description	Liquid Tight, Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.5mm, Inside Diameter 16.9mm, Static Bend Radius 80mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 10 Meters, Black

Ordering

EAN	5020963800702
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	8.77 lb 3.977 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	16.9 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.5 mm
Product Name	Flexible Metal Conduit
Product Type	Low Fire Hazard Conduit
Radius	80 mm
Special Functions	High UV Protection
UPC	786210289694

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SPL20/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SPL20/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available