

PRODUCT-DETAILS

# LFH-SPL25/25M

## 25MM LOW FIRE HAZARD LT COND 25M



Product image  
not available

### General Information

Extended Product Type	LFH-SPL25/25M
Product ID	7TCA296030R0406
EAN	5020963800733
Catalog Description	25MM LOW FIRE HAZARD LT COND 25M
Long Description	Liquid Tight, Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 25mm, Outside Diameter 26mm, Inside Diameter 21.4mm, Static Bend Radius 110mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 25 Meters, Black

### Ordering

EAN	5020963800733
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	29.76 lb 13.497 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

## Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	21.4 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	3/4 in NC25
Number of Batteries	0
Outside Diameter	26.0 mm
Product Name	Flexible Metal Conduit
Product Type	Low Fire Hazard Conduit
Radius	110 mm
Special Functions	High UV Protection
UPC	786210289724

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SPL25/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SPL25/25M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image  
not available