

PRODUCT-DETAILS

LFH-SPL32/25M

32MM LOW FIRE HAZARD LT COND 25M



Product image
not available

General Information

Extended Product Type	LFH-SPL32/25M
Product ID	7TCA296030R0408
EAN	5020963800757
Catalog Description	32MM LOW FIRE HAZARD LT COND 25M
Long Description	Liquid Tight, Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 32mm, Outside Diameter 34mm, Inside Diameter 28.1mm, Static Bend Radius 145mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 25 Meters, Black

Ordering

EAN	5020963800757
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	36.37 lb 16.494 kg

Container Information

Package Level 2 Units	5 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	28.1 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	1 in NC32
Number of Batteries	0
Outside Diameter	34.0 mm
Product Name	Flexible Metal Conduit
Product Type	Low Fire Hazard Conduit
Radius	145 mm
Special Functions	High UV Protection
UPC	786210289748

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SPL32/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SPL32/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available