

PRODUCT-DETAILS

# LFH-SPL40/10M

## 40MM LOW FIRE HAZARD LT CONDUIT



Product image  
not available

---

### General Information

Extended Product Type	LFH-SPL40/10M
Product ID	7TCA296030R0409
EAN	5020963800764
Catalog Description	40MM LOW FIRE HAZARD LT CONDUIT
Long Description	Liquid Tight, Low Fire Hazard, Medium Flexibility Conduit, Nominal Conduit Size 40mm, Outside Diameter 44.5mm, Inside Diameter 37.7mm, Static Bend Radius 180mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 10 Meters, Black

---

### Ordering

EAN	5020963800764
-----	---------------

---

### Dimensions

Product Net Depth / Length	10 m
Product Net Weight	31.01 lb 14.063 kg

---

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	37.7 mm
Material	Galvanized Steel Core with Low Fire Hazard Jacket
Nominal Size	1-1/4 in NC40
Number of Batteries	0
Outside Diameter	44.5 mm
Product Name	Flexible Metal Conduit
Product Type	Low Fire Hazard Conduit
Radius	180 mm
Special Functions	High UV Protection
UPC	786210289588

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SPL40/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SPL40/10M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image  
not available