

PRODUCT-DETAILS

SSPLHC20/25M

20MM STAINLESS CORE SPLHC



Product image
not available

General Information

Extended Product Type	SSPLHC20/25M
Product ID	7TCA296030R0416
EAN	5020963800917
Catalog Description	20MM STAINLESS CORE SPLHC
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Stainless Steel Core, Black

Ordering

EAN	5020963800917
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	21.22 lb 9.624 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	15.9 mm
Material	Stainless Steel Core with Thermoplastic Rubber Cover
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.1 mm
Product Name	Flexible Metal Conduit
Product Type	Extreme Temperature Flexible Conduit
Radius	80 mm
UPC	786210289793

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	7TKK001231
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SSPLHC20/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available