

PRODUCT-DETAILS

# SSPLHC25/25M

## 25MM STAINLESS CORE SPLHC



Product image  
not available

---

### General Information

Extended Product Type	SSPLHC25/25M
Product ID	7TCA296030R0417
EAN	5020963800924
Catalog Description	25MM STAINLESS CORE SPLHC
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 25mm, Outside Diameter 26.4mm, Inside Diameter 21.0mm, Static Bend Radius 110mm, Reel Length 25 Meters, Thermoplastic Rubber Cover with Stainless Steel Core, Black

---

### Ordering

EAN	5020963800924
-----	---------------

---

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	26.84 lb 12.172 kg

---

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	21.0 mm
Material	Stainless Steel Core with Thermoplastic Rubber Cover
Nominal Size	3/4 in NC25
Number of Batteries	0
Outside Diameter	26.4 mm
Product Name	Flexible Metal Conduit
Product Type	Extreme Temperature Flexible Conduit
Radius	110 mm
UPC	786210289809

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	7TKK001231
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SSPLHC25/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image  
not available