

PRODUCT-DETAILS

# SSPLHC50/10M

## 50MM STAINLESS CORE SPLHC



Product image  
not available

### General Information

Extended Product Type	SSPLHC50/10M
Product ID	7TCA296030R0420
EAN	5020963800955
Catalog Description	50MM STAINLESS CORE SPLHC
Long Description	Liquid Tight, Extreme Temperature Covered Steel Flexible Conduit, Medium Flexibility, Nominal Conduit Size 50mm, Outside Diameter 47.9mm, Inside Diameter 40.4mm, Static Bend Radius 240mm, Reel Length 10 Meters, Thermoplastic Rubber Cover with Stainless Steel Core, Black

### Ordering

EAN	5020963800955
-----	---------------

### Dimensions

Product Net Depth / Length	10 m
Product Net Weight	25.3 lb 11.474 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

### Additional Information

Application	Liquid Tight - Extreme Temperature Environments
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	40.4 mm
Material	Stainless Steel Core with Thermoplastic Rubber Cover
Nominal Size	1-1/2 in NC50
Number of Batteries	0
Outside Diameter	47.9 mm
Product Name	Flexible Metal Conduit
Product Type	Extreme Temperature Flexible Conduit
Radius	240 mm
UPC	786210289830

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	7TKK001231
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SSPLHC50/10M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image  
not available