

PRODUCT-DETAILS

SPUL20/BL/50M

SPUL20/BLACK CONDUIT X 50M



General Information

Extended Product Type	SPUL20/BL/50M
Product ID	7TCA296030R0426
EAN	5020963801174
Catalog Description	SPUL20/BLACK CONDUIT X 50M
Long Description	Liquid Tight, Medium Flexibility, Covered Steel Conduit, Nominal Conduit Size 20mm, Outside Diameter 21.1mm, Inside Diameter 15.9mm, Static Bend Radius 80mm, Reel Length 50 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Black

Ordering

EAN	5020963801174
-----	---------------

Dimensions

Product Net Depth / Length	50 m
Product Net Weight	44.75 lb 20.295 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Flexible Protection Systems
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	15.9 mm
Material	Galvanized Steel Core with PVC Cover and Copper Packing
Nominal Size	1/2 in NC20
Number of Batteries	0
Outside Diameter	21.1 mm
Product Name	FLEXIBLE CONDUIT
Product Type	Liquid Tight, Medium Flexibility Conduit
Radius	80 mm
Special Functions	High UV Protection
Standards	UL Listed, CSA
UPC	786210289540

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPUL20/BL/50M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPUL20/BL/50M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

