

PRODUCT-DETAILS

# SPUL40/BL/10M

## SPUL40/BLACK CONDUIT X 10M



Product image  
not available

### General Information

Extended Product Type	SPUL40/BL/10M
Product ID	7TCA296030R0430
EAN	5020963801211
Catalog Description	SPUL40/BLACK CONDUIT X 10M
Long Description	Liquid Tight, Medium Flexibility, Covered Steel Conduit, Nominal Conduit Size 40mm, Outside Diameter 41.8mm, Inside Diameter 35.4mm, Static Bend Radius 200mm, Reel Length 10 Meters, UL Listed and CSA Approved, PVC Covered Galvanised Steel Core with Copper Packing, Black

### Ordering

EAN	5020963801211
-----	---------------

### Dimensions

Product Net Depth / Length	10 m
Product Net Weight	31.01 lb 14.063 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

## Additional Information

Application	Flexible Protection Systems
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	35.4 mm
Material	Galvanized Steel Core with PVC Cover and Copper Packing
Nominal Size	1-1/4 in NC40
Number of Batteries	0
Outside Diameter	41.8 mm
Product Name	FLEXIBLE CONDUIT
Product Type	Liquid Tight, Medium Flexibility Conduit
Radius	200 mm
Special Functions	High UV Protection
Standards	UL Listed, CSA
UPC	786210288956

## Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPUL40/BL/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPUL40/BL/10M

## Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5543 >> Liquid Tight Conduit

## Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image  
not available