

PRODUCT-DETAILS

PFCSSS54/BL/25M

PF SS BRAID 54MM CONDUIT



Product image
not available

General Information

Extended Product Type	PFCSSS54/BL/25M
Product ID	7TCA296030R0435
EAN	5020963801341
Catalog Description	PF SS BRAID 54MM CONDUIT
Long Description	Standard Weight Conduit with Stainless Steel Braid, Nominal Conduit Size 54mm, NW Conduit Size 48, Coarse Conduit Pitch, Outside Diameter 54.5mm, Inside Diameter 46.6mm, Static Bend Radius 75mm, Reel Length 25 Meters, Modified Polyamide 12, Black

Ordering

EAN	5020963801341
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	50 lb 22.676 kg

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	1 piece

Package Level 2 Width	10 in 254 mm
Package Level 2 Height	37 in 940 mm
Package Level 2 Depth / Length	37 in 940 mm

Additional Information

Application	Rail Exterior
Brand / Label	Adaptaflex
Color	Black
Inside Diameter	46.6 mm
Material	Polyamide 12
Nominal Size	54 mm
Number of Batteries	0
Outside Diameter	54.5 mm
Product Name	FLEXIBLE METAL CONDUIT
Product Type	Standard Weight Conduit with Coarse Pitch and Stainless Steel Overbraid
Radius	75 mm
Special Functions	High Impact Resistance
UPC	786210289465

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	PFCSSS54/BL/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	PFCSSS54/BL/25M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available