

PRODUCT-DETAILS

LFH-SPSS50/10M

LFH SP50 WITH SS OVERBRAID



General Information

Extended Product Type	LFH-SPSS50/10M
Product ID	7TCA296040R0012
EAN	5020963797811
Catalog Description	LFH SP50 WITH SS OVERBRAID
Long Description	Low Fire Hazard, Medium Flexibility Conduit with Stainless Steel Overbraid, Nominal Conduit Size 50mm, Outside Diameter 55.0mm, Inside Diameter 48.4mm, Static Bend Radius 240mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 10 Meters, Black

Ordering

EAN	5020963797811
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	1 lb 453.515 g

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in

	25 mm
Package Level 2 Height	1 in
	25 mm
Package Level 2 Depth / Length	1 in
	25 mm

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Brand / Label	Adaptaflex
Color	Black
Flexibility	Medium
Inside Diameter	48.4 mm
Material	Galvanized Steel Core with LFH Jacket and Stainless Steel Overbraid
Number of Batteries	0
Outside Diameter	55.0 mm
Product Name	PIPE/TUBE WITH FITTINGS
Product Type	Medium Flexibility Conduit
Radius	240 mm
Special Functions	High UV Protection, Low Fire Hazard
UPC	786210293219

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	7TK001224
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	LFH-SPSS50/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

