

PRODUCT-DETAILS

SB10/25M

STEEL BRAIDED COND NC10 25M



General Information

Extended Product Type	SB10/25M
Product ID	7TCA296040R0014
EAN	5020963061271
Catalog Description	STEEL BRAIDED COND NC10 25M
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 10mm, Outside Diameter 10.0mm, Inside Diameter 6.8mm, Static Bend Radius 25mm, Reel Length 25 Meters, Galvanised Steel Core and Overbraid

Ordering

EAN	5020963061271
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	11.13 lb 5.048 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	6.8 mm
Material	Galvanized Steel Core and Overbraid
Nominal Size	1/4 in 10 mm
Number of Batteries	0
Outside Diameter	10.0 mm
Product Name	FLEX CONDUIT
Product Type	Low Fire Hazard Conduit
Radius	25 mm
Special Functions	Very High UV Protection and High Fatigue Life
UPC	786210275598

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SB10/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SB10/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

