

PRODUCT-DETAILS

SB25/25M

STEEL BRAIDED COND NC25 25M



General Information

Extended Product Type	SB25/25M
Product ID	7TCA296040R0051
EAN	5020963003844
Catalog Description	STEEL BRAIDED COND NC25 25M
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 25mm, Outside Diameter 26.0mm, Inside Diameter 21.4mm, Static Bend Radius 55mm, Reel Length 25 Meters, Galvanised Steel Core and Overbraid

Ordering

EAN	5020963003844
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	15.43 lb 6.998 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	9.5 in 241 mm

Package Level 1 Height	25 in 635 mm
Package Level 1 Depth / Length	25 in 635 mm
Package Level 2 Units	10 piece
Package Level 2 Width	9.5 in 241 mm
Package Level 2 Height	26 in 660 mm
Package Level 2 Depth / Length	25 in 635 mm

Additional Information

Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	21.4 mm
Material	Galvanized Steel Core and Overbraid
Nominal Size	3/4 in
Number of Batteries	0
Outside Diameter	26.0 mm
Product Name	flexible metal conduit
Product Type	Low Fire Hazard Conduit
Radius	55 mm
Special Functions	Very High UV Protection and High Fatigue Life
UPC	786210244303

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SB25/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SB25/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

