

PRODUCT-DETAILS

# SB40/25M

## S40 BRAIDED CONDUIT 25M REELS



### General Information

Extended Product Type	SB40/25M
Product ID	7TCA296040R0074
EAN	5020963033766
Catalog Description	S40 BRAIDED CONDUIT 25M REELS
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 40mm, Outside Diameter 43.6mm, Inside Diameter 37.7mm, Static Bend Radius 80mm, Reel Length 25 Meters, Galvanised Steel Core and Overbraid

### Ordering

EAN	5020963033766
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	41.28 lb 18.721 kg

### Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

### Additional Information

Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	37.7 mm
Material	Galvanized Steel Core and Overbraid
Nominal Size	1-1/4 in
Number of Batteries	0
Outside Diameter	43.6 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	80 mm
Special Functions	Very High UV Protection and High Fatigue Life
UPC	786210274027

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SB40/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SB40/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

