

PRODUCT-DETAILS

SB50/25M

S50 BRAIDED CONDUIT 25M REELS



General Information

Extended Product Type	SB50/25M
Product ID	7TCA296040R0081
EAN	5020963033896
Catalog Description	S50 BRAIDED CONDUIT 25M REELS
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 50mm, Outside Diameter 56.0mm, Inside Diameter 48.4mm, Static Bend Radius 90mm, Reel Length 25 Meters, Galvanised Steel Core and Overbraid

Ordering

EAN	5020963033896
-----	---------------

Dimensions

Product Net Depth / Length	25 m
Product Net Weight	51.75 lb 23.469 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	48.4 mm
Material	Galvanized Steel Core and Overbraid
Nominal Size	1-1/2 in
Number of Batteries	0
Outside Diameter	56.0 mm
Product Name	ADAPTAFLEX
Product Type	Low Fire Hazard Conduit
Radius	90 mm
Special Functions	Very High UV Protection and High Fatigue Life
UPC	786210274546

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SB50/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SB50/25M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

