

PRODUCT-DETAILS

SB63/10M

STEEL BRAIDED COND NC63 10M



General Information

Extended Product Type	SB63/10M
Product ID	7TCA296040R0089
EAN	5020963050305
Catalog Description	STEEL BRAIDED COND NC63 10M
Long Description	Low Fire Hazard, High Flexibility, Covered Steel Conduit, Nominal Conduit Size 63mm, Outside Diameter 63.5mm, Inside Diameter 57.5mm, Static Bend Radius 115mm, Reel Length 10 Meters, Galvanised Steel Core and Overbraid

Ordering

EAN	5020963050305
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	11.46 lb 5.197 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Standard EMI Screen - Very High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Inside Diameter	57.5 mm
Material	Galvanized Steel Core and Overbraid
Nominal Size	2 in
Number of Batteries	0
Outside Diameter	63.5 mm
Product Name	flex metal conduit
Product Type	Low Fire Hazard Conduit
Radius	115 mm
Special Functions	Very High UV Protection and High Fatigue Life
UPC	786210245058

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SB63/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SB63/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

