

PRODUCT-DETAILS

SPB20/10M

GALVANIZED STEEL BRAIDED SP CONDUIT



General Information

Extended Product Type	SPB20/10M
Product ID	7TCA296040R0119
EAN	5020963040368
Catalog Description	GALVANIZED STEEL BRAIDED SP CONDUIT
Long Description	Highly Flexible Steel Conduit, Nominal Conduit Size 20mm, Outer Diameter 21.5mm, Inner Diameter 16.9mm, Maximum Bend Radius 45mm, Reel Length 10 Meters, Galvanised Steel Core with PVC Jacket and Galvanised Steel Overbraid

Ordering

EAN	5020963040368
-----	---------------

Dimensions

Product Net Depth / Length	10 m
Product Net Weight	6.61 lb 2.998 kg

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Material	Galvanized Steel Core and Overbraid with PVC Jacket
Nominal Size	1/2 in
Number of Batteries	0
Product Name	FLEX TUBING OF STEEL W/O FITTINGS
Product Type	High Flexibility Conduit
Radius	45 mm
Special Functions	Very High UV Protection
UPC	786210295121

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPB20/10M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPB20/10M

Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

