

PRODUCT-DETAILS

# SPB25/25M

## STEEL/PVC/BRAID COND NC25 25M



### General Information

Extended Product Type	SPB25/25M
Product ID	7TCA296040R0135
EAN	5020963004469
Catalog Description	STEEL/PVC/BRAID COND NC25 25M
Long Description	Highly Flexible Steel Conduit, Nominal Conduit Size 25mm, Outer Diameter 26.0mm, Inner Diameter 21.4mm, Maximum Bend Radius 55mm, Reel Length 25 Meters, Galvanised Steel Core with PVC Jacket and Galvanised Steel Overbraid

### Ordering

EAN	5020963004469
-----	---------------

### Dimensions

Product Net Depth / Length	25 m
Product Net Weight	38.91 lb 17.646 kg

### Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	40 in 1016 mm

Package Level 1 Height	50 in 1270 mm
Package Level 1 Depth / Length	48 in 1219 mm
Package Level 2 Units	5 piece
Package Level 2 Width	40 in 1016 mm
Package Level 2 Height	50 in 1270 mm
Package Level 2 Depth / Length	48 in 1219 mm
Package Level 3 Units	5 piece
Package Level 3 Width	40 in 1016 mm
Package Level 3 Height	50 in 1270 mm
Package Level 3 Depth / Length	48 in 1219 mm

### Additional Information

Application	Indoors / Outdoors - Enhanced EMI Screen - High Abrasion Resistance
Brand / Label	Adaptaflex
Flexibility	High
Material	Galvanized Steel Core and Overbraid with PVC Jacket
Nominal Size	3/4 in
Number of Batteries	0
Product Name	flexible metal conduit
Product Type	High Flexibility Conduit
Radius	55 mm
Special Functions	Very High UV Protection
UPC	786210245287

### Certificates and Declarations (Document Number)

Data Sheet, Technical Information	SPB25/25M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPB25/25M

### Classifications

ETIM 6	EC001179 - Protective metallic hose
ETIM 7	EC001179 - Protective metallic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

### Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

