

PRODUCT-DETAILS

# SPB25/M25/B

## SWVL MALE BR IP54 ADPTR NC25 M25



### General Information

Extended Product Type	SPB25/M25/B
Product ID	7TCA296040R0141
EAN	5020963008627
Catalog Description	SWVL MALE BR IP54 ADPTR NC25 M25
Long Description	Nickel Plated Brass Straight Fitting with Swivel External Thread, Nominal Conduit Size 25 Millimeters, IP54 Rating, Metric Thread Size M25

### Ordering

EAN	5020963008627
-----	---------------

### Dimensions

Product Net Weight	.21 lb 95.238 g
--------------------	--------------------

### Container Information

Package Level 2 Units	10 piece
Package Level 2 Width	1 in 25 mm
Package Level 2 Height	1 in 25 mm

Package Level 2 Depth / Length	1 in 25 mm
--------------------------------	---------------

**Additional Information**

Application	For Insertion into Threaded Entries or Knockout to Connect Conduit
Brand / Label	Adaptaflex
Cable Entry Position	M25 Thread
Color	Metallic
Material	Brass
Number of Batteries	0
Product Name	brass fitting for conduit
Product Type	Conduit Fitting with Metric Threads
Size	3/4 Inch
Surface Finishing	Nickel Plated
UPC	786210245270

**Certificates and Declarations (Document Number)**

Data Sheet, Technical Information	SPB25/M25/B
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	SPB25/M25/B

**Classifications**

ETIM 6	EC001180 - Screw connection for protective metallic hose
ETIM 7	EC001180 - Screw connection for protective metallic hose
UNSPSC	39121311
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4441 >> Electrical fittings

**Categories**

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

